

Thermo Scientific Orion Star A213

Advanced RDO/dissolved oxygen benchtop meter

The Thermo Scientific™ Orion™ Star A213 RDO/Dissolved Oxygen Benchtop Meter works for any lab or application. Its durability and dependability make it ideal for every BOD sample, every day.



The Thermo Scientific Orion Star A213 RDO/Dissolved Oxygen (DO) Benchtop Meter is the ideal choice for any lab. Get the information you need quickly and easily from the large, backlit graphic LCD display. Informative display shows dissolved oxygen in percent saturation or concentration and temperature with time, date, sample ID, user ID and compensation settings.

Features and Benefits

- Easy meter operation assured with on-screen text prompts, menu-specific function keys and a multi-language interface
- Compatible with Orion RDO optical and Orion polarographic DO probes
- Accurate results are easy with automatic temperature, manual salinity and automatic/manual barometric pressure compensation
- Don't miss a reading—AUTO-READ™ locks the stable reading on screen, ready indicator alerts when reading is stable and timed setting logs data at set intervals

- Calibrate using water-saturated air, air-saturated water, custom value using a Winkler titration or zero point calibration
- Non-volatile memory holds up to 2000 data points with time and date stamp
- Easily transfer data with the USB and RS232 ports and complimentary Orion Star Com computer software
- For faster BOD readings, control the Thermo Scientific™ Orion™ AUTO-STIR™ DO/BOD probe (086030MD) directly from the meter
- Included electrode arm and holder make it easier to maintain and place probes into samples
- IP54-rated housing handles splashes and is wall-mountable to save space
- 3 year meter replacement warranty

Thermo
SCIENTIFIC

Thermo Scientific Orion Star A213 RDO/Dissolved Oxygen Benchtop Meter

Specifications	
Dissolved Oxygen	<p>Concentration—Polarographic Range: 0 to 90 mg/L Resolution: 0.01, 0.1 mg/L Relative Accuracy: ± 0.2 mg/L or ± 2 % of reading, whichever is greater</p> <p>% Saturation—Polarographic Range: 0 to 600 % saturation Resolution: 0.1, 1 % saturation Relative Accuracy: ± 2 % saturation or ± 2 % of reading, whichever is greater</p> <p>Concentration—RDO Range: 0 to 50 mg/L Resolution: 0.01, 0.1 mg/L Relative Accuracy: ± 0.1 mg/L up to 8 mg/L; ± 0.2 mg/L from 8 to 20 mg/L; 10 % of reading from 20 to 50 mg/L</p> <p>% Saturation—RDO Range: 0 to 500 % saturation Resolution: 0.1, 1 % saturation Relative Accuracy: ± 2 % sat. ≤ 200 % sat., ± 10 % sat. > 200 % sat.</p> <p>Barometric Pressure Correction: 400 to 850 mmHg, automatic or manual</p> <p>Manual Salinity Factor Correction: 0 to 45 ppt</p> <p>Calibration Features: Water-saturated air, air saturated water, manual (Winkler) and zero point</p>
Temperature	<p>Range: 0 to 50 °C, 32 to 122 °F Resolution: 0.1 °C, 0.1 °F Relative Accuracy: ± 0.1 °C, ± 0.1 °F Offset Calibration: 1 point</p>
Datalogging	<p>Memory: 2000 with time and date stamp Log Function: Manual, ready (includes AUTO-READ), timed</p>
Inputs	<p>DO Probe with Built-in Temperature: 9-pin mini-DIN</p>
Output	<p>RS232, USB</p>
Power	<p>AC Adapter: Included—universal, 100-240 VAC Battery Power: Optional—4 AAs Battery Life: 800 hrs</p>

 **Thermo Fisher Scientific**
 Water Analysis Instruments
 Chelmsford, MA USA
 Quality Management System
 Registered to ISO 9001

thermoscientific.com/water

© 2013 Thermo Fisher Scientific Inc. All rights reserved. Certified System StandardsMark logo is a trademark of SAI Global. All other trademarks are the property of Thermo Fisher Scientific Inc. & its subsidiaries

Water Analysis Instruments

North America
 Toll Free: 1-800-225-1480
 Tel: 1-978-232-6000
 info.water@thermo.com

Netherlands
 Tel: (31) 020-4936270
 info.water.uk@thermo.com

China
 Tel: (86) 21-68654588
 wai.asia@thermofisher.com

India
 Tel: (91) 22-4157-8800
 wai.asia@thermofisher.com

Singapore
 Tel: (65) 6778-6876
 wai.asia@thermofisher.com


Meter Ordering Information

Part No.	Description
STARA2130	<p>Orion Star A213 Dissolved Oxygen Benchtop Meter</p> <ul style="list-style-type: none"> - Attached electrode stand and holder - Universal power adapter - Printed quick start guide and literature CD - USB computer cable
STARA2135	<p>Orion Star A213 Dissolved Oxygen Benchtop Meter Kit</p> <ul style="list-style-type: none"> - 083005MD Orion polarographic DO probe with calibration sleeve - 080513 DO probe maintenance kit - BOD adapter, funnel and stirrer - Attached electrode stand and holder - Universal power adapter - Printed quick start guide and literature CD - USB computer cable
STARA2136	<p>Orion Star A213 Dissolved Oxygen Benchtop Meter Kit with Self-Stirring Probe</p> <ul style="list-style-type: none"> - 086030MD Orion polarographic AUTO-STIR DO/BOD probe - 080513 DO probe maintenance kit - 080514 DO probe electrolyte - Attached electrode stand and holder - Universal power adapter - Printed quick start guide and literature CD - USB computer cable

Accessories Ordering Information

Part No.	Description
STARA-BEA	Orion Star A series electrode arm, holder and benchtop meter-attachable base plate
STARA-HB	Orion Star A series freestanding base for electrode arm and holder
083005MD	Orion polarographic DO probe, 1.5 m cable
086030MD	Orion polarographic AUTO-STIR DO/BOD probe, 1.5 m cable
087010MD	Orion RDO optical DO probe, 3 m cable with stainless steel guard and calibration sleeve
080513	Orion polarographic DO probe maintenance kit
080514	Orion polarographic DO probe electrolyte solution, 60 mL
087003	Replacement calibration sleeve for Orion RDO optical probes
087001	Replacement optical cap for Orion RDO probes

For more information, contact your local Thermo Scientific products dealer or call our customer and technical service experts at 1-800-225-1480 (for the US and Canada) or visit www.thermoscientific.com/water.



Redesigned electrode arm and holder



Thermo
 SCIENTIFIC

Part of Thermo Fisher Scientific

Japan
 Tel: (81) 045-453-9175
 wai.asia@thermofisher.com

Australia
 Tel: (613) 9757-4300
 in Australia (1300) 735-295
 InfoWaterAU@thermofisher.com